



Jednofázový motor				
Rozměry a hmotnost				
Typ čerpadla	Rozměry (mm)			
	A	B	C	D
ST-1005	236	RP/ NPT 1 1/4"	98	582
ST-1007	271		98	617
ST-1010	324		98	689
ST-1014	394		98	774
ST-1020	499		98	904

Třífázový motor				
Rozměry a hmotnost				
Typ čerpadla	Rozměry (mm)			
	A	B	C	D
ST-1005	236	RP/ NPT 1 1/4"	98	566
ST-1007	271		98	601
ST-1010	324		98	670
ST-1014	394		98	759
ST-1020	499		98	879

## Tabulka pro výběr

TYP ČERPADLA	STUPNĚ	MOTOR		Q=VÝTLAK												ČERPA DLO	ELEKTRO ČERPADLO	
				KW	HP	l/min	0	10	15	20	25	30	35	40	45		50	60
		m³/h	0	0.6	0.9	1.2	1.5	1.8	2.1	2.4	2.7	3.0	3.6					
		H=VÝTLAČNÁ VÝŠKA V METRECH																
ST-1005	5	0.37	0.5	34		32	31	29	27	25	23	19	16		2.5	9.8	9.2	
ST-1007	7	0.37	0.5	46		43	42	39	36	33	29	26	22		2.8	10.1	9.5	
ST-1010	10	0.55	0.75	67		64	61	58	54	49	43	36	28		3.3	11.5	10.7	
ST-1014	14	0.75	1.0	92		86	83	79	74	67	60	52	42		3.9	12.7	12.1	
ST-1020	20	1.1	1.5	139		131	127	120	111	101	90	75	60		4.9	14.9	13.8	